

Date of valid edition
2017-03-24

No:
5081

Date of first issue
2008-10-23

Reference

Name and address of certificate holder

Uponor AB
Box 101
730 61 Virsbo

Conformity mark covered by certificate



Information regarding certificate holder/manufacturer

Contact person Katharina Kölking	Telephone +46 223 38 11	Telefax -
	E-mail katharina.kolking@uponor.com	
Manufacturer Uponor AB	Place of manufacture Virsbo, Sweden	

Product covered by the certificate

Type of product	Standard Normative document	Specific rules					
Plastics piping systems for hot and cold water installations – Crosslinked polyethylene (PE-X) – Part 2: Pipes.	EN ISO 15875-2:2003	INSTA SBC 15875					
Specification of product							
<table border="1"> <tr> <td> Uponor combiPEX (Q&E) Application class 2 Dim class B1 Pipes with diffusion barrier 15x2.5 18x2.5 22x3.0 28x4.0 </td> <td> Uponor combiPEX (Q&E) Application class 2 and 5 Dim class A Pipes with diffusion barrier 12x1.7 16x2.2 20x2.8 25x3.5 </td> <td> Uponor PEX (Wirsbo-PEX) Application class 2 Dim class B1 10x1.8 15x2.5 18x2.5 22x3.0 28x4.0 </td> <td> Uponor Combi pipe Application class 2/10 and 5/8 bar Dim class C Pipes with diffusion barrier 16x2.0 </td> <td> Uponor PEX (Wirsbo-PEX) Application class 2 Dim class A Pipe series S 3.2 Size group 1 and 2 12x1.7 16x2.2 20x2.8 25x3.5 32x4.4 40x5.5 50x6.9 63x8.6 75x10.3 90x12.3 110x15.1 </td> </tr> </table>	Uponor combiPEX (Q&E) Application class 2 Dim class B1 Pipes with diffusion barrier 15x2.5 18x2.5 22x3.0 28x4.0	Uponor combiPEX (Q&E) Application class 2 and 5 Dim class A Pipes with diffusion barrier 12x1.7 16x2.2 20x2.8 25x3.5	Uponor PEX (Wirsbo-PEX) Application class 2 Dim class B1 10x1.8 15x2.5 18x2.5 22x3.0 28x4.0	Uponor Combi pipe Application class 2/10 and 5/8 bar Dim class C Pipes with diffusion barrier 16x2.0	Uponor PEX (Wirsbo-PEX) Application class 2 Dim class A Pipe series S 3.2 Size group 1 and 2 12x1.7 16x2.2 20x2.8 25x3.5 32x4.4 40x5.5 50x6.9 63x8.6 75x10.3 90x12.3 110x15.1	Application class 2: Hot water supply (70°C), 10 bar Application class 5: High temperature radiators, 6 or 10 bar Confidential information according to the enclosure	
Uponor combiPEX (Q&E) Application class 2 Dim class B1 Pipes with diffusion barrier 15x2.5 18x2.5 22x3.0 28x4.0	Uponor combiPEX (Q&E) Application class 2 and 5 Dim class A Pipes with diffusion barrier 12x1.7 16x2.2 20x2.8 25x3.5	Uponor PEX (Wirsbo-PEX) Application class 2 Dim class B1 10x1.8 15x2.5 18x2.5 22x3.0 28x4.0	Uponor Combi pipe Application class 2/10 and 5/8 bar Dim class C Pipes with diffusion barrier 16x2.0	Uponor PEX (Wirsbo-PEX) Application class 2 Dim class A Pipe series S 3.2 Size group 1 and 2 12x1.7 16x2.2 20x2.8 25x3.5 32x4.4 40x5.5 50x6.9 63x8.6 75x10.3 90x12.3 110x15.1			

The certificate holder above is hereby given permission to use the INSTA-CERT mark on or in connection with products, which fulfil the requirements of the standard or the normative document specified above (what is said in this document about INSTA-CERT mark will also be valid for marks defined in relevant SBC). The certificate is valid on the condition that the certificate holder complies with the "General rules for certification by partners of INSTA-CERT" (GRC) and the specific rules applying to certification of products of the type mentioned. The certificate holder is obliged to indemnify INSTA-CERT partners of any claim for damages or any other expenses to which partners may become liable as a result of injuries caused by a product manufactured or sold by the licensee. This also applies to defective or faulty products.

Unless terminated, the certificate will be automatically extended for one year at a time. The certificate will be re-issued with a new "date of valid edition" only if the content and/or conditions of the certificate have been changed. Termination may take place to the end of a year subject to three months' notice on the part of the certificate holder and the certification body.

The certificate is not transferable.

MEMBER OF INSTA-CERT

SP Sveriges Tekniska Forskningsinstitut

Lennart Månsson